



NON SLIP

safety products

5-8 Chilford Court, Rayne Rd
Braintree, Essex,
CM7 2QS

Tel: 01376 333315
Fax: 01376 551849
e-mail: sales@nonslipsp.co.uk
www.nonslipsp.co.uk

Guide for Installing “Safe-Grip”

Recommended Procedures:

1. Ensure that the ladder rungs are clean and free of loose paint etc. Wipe the rungs with a suitable solvent cleaner to remove any grease and similar dirt likely to prevent a suitable adhesion.
2. Remove the “Safe-Grips” from the pack and abrade the internal surface so as to provide a good key for the adhesive. Using a clean rag, remove all dust residue etc.
3. Insert a cartridge of 3M 5200 FC polyurethane adhesive sealant into a cartridge gun and screw the nozzle on to the cartridge.
4. Cut approximately 20mm from the end of the nozzle leaving a hole of about 6mm in diameter.
5. Apply a 6mm diameter bead of 3M 5200 FC down the middle of each internal surface of the “Safe-Grip” profiles. Do not apply 3M 5200 FC to more than 5 “Safe-Grips” at a time.
6. Starting with the top ladder rung, place a “Safe-Grip” over it and while swivelling it back and forth, apply a downward pressure until the 3M 5200 FC oozes out at each end.
7. Ensure that the top surface of the “Safe-Grip” is horizontal and remove any excess 3M 5200 FC from the rung.
8. Ensure that the rest of the ladder rungs are still clean and repeat procedures 6 & 7.
9. When completed do not allow the ladder to be used for a minimum of 24 hours.
10. Regardless of the cure time allowed, **do not** put the ladder back into service until all “Safe-Grip” profiles have been checked and confirmed as secure.

Please ensure that the 3M 5200 FC data sheets are studied before commencing the installation. Local conditions and circumstances may require some amendments.

PLEASE ENSURE THAT EXTREME CAUTION IS TAKEN WHILST WORKING ON LADDERS AND THAT THE APPROPRIATE PPE IS ALWAYS WORN.

*If you have any queries or simply require some advise, please feel free to call us on
01376 333315*